

7.1 合成单酯

产品 **ESTILUBE L 245**

特性 **ESTILUBE L 245** 是强极性单酯，具有高闪点，优异的水解稳定性和润湿性以及良好的环境相容性。

数据资料		典型 数值	规格		
			最少	最大	
外观	:	清晰			visual
色度	:	30		60	ISO 6271
密度 20°C (g/ml)	:	0.865	0.855	0.875	DIN 51757 (4)
酸值(mg KOH/g)	:	0.1		2.0	DIN 51 558-1
闪点(°C)	:	130	100		ISO 2719
倾点 (°C)	:	< -30			ISO 3016
粘度 25°C (mPa·s)	:	5			ISO 3104
碘值 (g I ₂ /100 g)	:	< 1			DGF CV 11d

应用 **推荐 ESTILUBE L 245 作为基础油或配方成分用于:**

- 金属加工油
- 渗透和防锈油
- 工业清洁剂，代替白油或异链烷烃
- 脱水液和快速分离的冷清洗剂
- 脱模剂

存储 **ESTILUBE L 245 可以在原装密封条件下在+10°C 到+30°C 存储至少 12 个月。**

The data contained herein serve as general information for our customers only and are not binding. The data contained herein have been collected to the best of our knowledge and do not constitute any advice or warranty to our customers for any specific application. It is up to our customer at their own risk to determine the suitability of each product for their individual purposes. The products are sold without any representation, warranty or guarantee either expressed or implied. Our liability is limited to the value of the supplied merchandise.